

TRIAX AGRA STOU

TRANSMISSION & HYDRAULIC OIL FOR AGRICULTURAL EQUIPMENT

TRIAX Agra STOU 10W-30 and 10W-40 is a premium quality multipurpose "One Fluid" lubricant which has been developed to meet the lubrication requirements of diesel and gasoline engines and be used as transmission, hydraulic, final drive lubricant for most modern farming equipment. Offers exceptional low temperature performance vs standard tractor fluids and considerably better wear protection for hydraulic systems, valves, pumps, hoses. Variable viscosity characteristics make it possible to use in both very high and very low ambient temperatures.

PERFORMANCE HIGHLIGHTS

- Superior protection for ultra-heavy, high dust, high temperature work environments
- Superior viscosity stability excellent protection against oxidative thickening
- High VI Index maximizes fluid stability during long operating hours and high temperature operations
- Superior resistance to contamination
- Excellent resistance to water contamination
- Exceptional resistance to contamination and superior soot / viscosity control
- High TBN protects against acid buildup and corrosion
- High foaming resistance, contains foam inhibitors
- Superior protection for hydraulic seal integrity and hydraulic pump parts
- Outstanding deposit control and hydraulic system cleanliness
- High levels of Zinc and Phosphorus for maximum anti-wear protection
- Facilitates the smooth operations of wet brake systems, preventing chatter and glazing

APPLICATIONS

TRIAX AGRA STOU fluids are designed for most agricultural equipment transmissions and hydraulic systems requiring an high performance EP (Extreme Pressure) API GL-4 10W30 (ISO 32, 46) fluid. These products are also designed to be used as engine oils in equipment requiring a CH-4 / CI-4 (Agri applications only).

SPECIFICATIONS

VISCOSITY GRADE 10W-30 and 10W-40

CASE-IH MS-1204,6,7,9 - Massey Ferguson M 1139 / 1144 / 1145 - MB 227.1 / MB 228.1 - Case New Holland MAT 3525 / 3526 - Ford M2C-159-B, C , Ford NH 82009201,2,3 , Ford M2C86B,C, 134D, - Caterpillar TO-2, John Deere JDM J27 - ZF TE-ML-06A,B,C,R, 07B - Allison C3, C4 API GL-4 - HVLP-D 68 - DIN 51 524 - 3 MIL-L 2104 D, MIL-L 2105, MIL-L 46152 B, ZF TE-ML 06B, ZF TE-ML 07B

CVT / VARIO Applications for 10W-40

TRIAX AGRA STOU 10W-40 is approved for use in modern CVT / Vario (Variable) high efficiency electronic transmissions fitted on new equipment, such as Deutz Fahr, Kubota, John Deere, Fend, CASE, CLAAS Axion, Massey Ferguson and many others.

ENGINE APPLICATIONS

ACEA E2, ACEA E3, Allison C4, API CF-4, Caterpillar TO-2, Mack EO-K, Mack EO-K2,

If a specification is listed above, TRIAX LLC guarantees the product meets, exceeds that specification or recommends the product for use in that specification. Our product warranty covers those applications.

CHEMICAL PROPERTIES

PROPERTY	Viscosity 10W-30	10W-40
SPECIFIC GRAVITY @ 60F	0.841	0.856
KINEMATIC VISCOSITY @ 40C	71	92
KINEMATIC VISCOSITY @ 100 C	10.75	14
VISCOSITY INDEX	140	156
FLASH POINT (C)	232	232
POUR POINT C(F)	-45 (-49)	-35 (-31)
TBN	10	10

Small deviations from these results are expected during the manufacturing process and do not affect product performance.

*All trademarked names are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use, which is strictly to guide consumers as to the application of TRIAX products and convey compatibility or lack thereof.

** The drain interval mentioned herein represents the capability of the lubricant and is valid for a mechanically sound engines, with regular oil analysis and without the use of after-market additives.