

TRIAX EURO CAR ATF

FULL SYNTHETIC EUROPEAN CAR LOW VISCOSITY ATF FOR ZF 6-8-9 SPEED TRANSMISSIONS

TRIAX Euro Car ATF very low viscosity, ultra fluid ATF designed for use in sequential shift automatic gear boxes of most European cars requiring a low viscosity ATF. This particular fluid was designed to meet the advanced specification requirements of high performance ZF 7, 8 and 9 speed transmissions.

This fluid qualifies for FILL FOR LIFE service in properly sealed transmissions, if the OEM does not require a particular drain interval in the OEM manual.

PERFORMANCE HIGHLIGHTS

- Excellent cold temperature performance down to - 60 F
- High load capacity and significant wear reduction
- Provides a wide range of seal compatibility with all types of materials
- Provides excellent wear protection and good lubrication properties
- Possesses excellent frictional characteristics for smoother shifting and quieter operation
- Prevents rust and oxidation
- Very high viscosity index for superior viscosity stability
- No foaming
- Smooth clutch engagement
- Flawless shifting characteristics for rapid gear changes (sports driving)
- Wide range compatibility across multiple OEMs

SPECIFICATIONS & APPLICATIONS

All ZF 6, 8 and 9 speed transmissions in modern European cars. This includes many BMW, Audi, VW, Mercedes, Skoda, Seat, Porsche and Land Rover vehicles.

DO NOT USE IN CVT OR DUAL CLUCH TRANSMISSIONS

SPECIFICATIONS:

- BMW L12108 (83 22 2 152 426)
- BMW 83 22 2 305 397
- BMW 83 22 2 289 720
- Chrysler 68157995AA
- Jaguar 02JDE 26444
- Land Rover LR 023288
- VW / Audi G 060 162 A1/A2/A6,
- VW / Audi G 055 162 (A2, A6),
- VW G 055 162
- ZF Lifeguard fluid 8 (S671 090 312)
- ATF L 12108
- Fiat 9.55550-AV5
- Honda 08200-9017, ATF Type 3.1
- Acura ATF Type 3.0, Acura 08200-9016A
- LR023288, LR023289
- Mopar 68218925AA, 68157995AB
- ZF S671 090 312, ZF TE-ML 11 9HP48, Lifeguard 6, Lifeguard 8
- For ZF 6, 8 and 9 speed transmissions in modern European cars

If a specification is listed above, TRIAX LLC guarantees the product meets, exceeds that specification or is safe to use in equipment requiring that application, and is therefore covered by our product warranty.

CHEMICAL PROPERTIES

Viscosity @ 100°C, cSt, ASTM D445	5.5
Viscosity @ 40°C, cSt, ASTM D445	24.5
Viscosity Index, ASTM D2270	172
Pour Point, °C, ASTM D97	-51
Flash Point, °C(F), ASTM D92	221 (430)
Specific Gravity	0.845

Small deviations from these results are expected during the manufacturing process and do not affect product performance or specification compliance.

All trademarked names are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use, which is strictly to guide consumers as to the application of TRIAX products and convey compatibility or lack thereof.