



TRIAX Euro VX 5W-30

Full-Synthetic Mid-SAPS Engine Oil — For European Diesel (DPF) & Gasoline Engines Requiring SAE 5W-30 ACEA C3

Rev: May 19, 2026

DESCRIPTION

TRIAX Euro VX 5W-30 is a friction-modified, low-ash, long-life full-synthetic engine oil with the widest application range in the TRIAX European line. Specifically designed for European gasoline and diesel cars (with DPF) — with emphasis on ultra-high-performance, high-compression European diesels — it combines low volatility, exceptionally high wear protection, and excellent thermal stability under severe stress. The mid-SAPS formulation delivers considerable oil longevity (exceeding 15,000 miles / ~25,000 km), excellent detergency, sludge control, and oxidation stability, while ensuring complete compatibility with diesel particulate filters (DPF) and SCR (AdBlue) emissions systems.

PERFORMANCE HIGHLIGHTS

- Extreme durability and shear stability — long-lasting protection for high-horsepower, high-performance European engines
- **Up to 90% less** deposits vs. ACEA C3-16 standards* and **up to 70% less** cam wear vs. industry standards**
- **State-of-the-art detergent system** keeps engines clean for 250,000 miles and beyond — near-zero deposits on piston rings and valves throughout its life
- Very low friction coefficient minimizes engine wear; exceptionally quiet and efficient hydraulic tappet operation
- Unmatched turbocharger protection — prevents coking and deposit-related failure in high-output turbo engines
- Mid-SAPS (sulfated ash < 0.8%) chemistry provides complete protection for catalytic converters, diesel particulate filters (DPF), and SCR (AdBlue) systems
- Maintains film integrity even at high operating temperatures under severe stress

*Based on Mercedes-Benz M271 sludge test using 5W-30. **Based on Mercedes-Benz OM646LA engine test using 5W-30; drain interval represents the lubricant's capability under normal duty in a mechanically sound engine with regular oil analysis and no aftermarket additives. Always consult the vehicle owner's manual.

SPECIFICATIONS & APPLICATIONS

TRIAX Euro VX 5W-30 is designed for a wide range of Mercedes-Benz, VW, Audi, and BMW diesel and gasoline vehicles, SUVs, and light trucks requiring an ACEA C3, VW 507.00, or VW 504.00 mid-SAPS engine oil — including diesel vehicles fitted with DPF and SCR emissions systems. Also suitable for any application requiring an ACEA C2 oil, or US vehicles requiring API SP / SN Plus.

For applications requiring the following specifications:

- ACEA C3
- VW 504 00, VW 507 00
- BMW LL-04 (DPF)
- Mercedes-Benz MB 229.31, 229.52, 229.51
- Porsche C30
- VW 500 00, 501 01, 502 00
- Opel OV 040 1547-G30 / OV 040 1547 D30
- Chrysler MS-13340
- API SP

Also Recommended For:

- ACEA C2 (suitable for use)
- BMW LL-01, LL-01 FE (up to 2018)
- Fiat 9.55535-S1, 9.55535-S3
- VW 503 00/01, 505 00/01, 506 00/01; GWM / Haval

TYPICAL PROPERTIES

Parameter	TRIAX Euro VX 5W-30	Test Method
Viscosity, Kinematic @ 40 °C, cSt	69	ASTM D445
Viscosity, Kinematic @ 100 °C, cSt	12	ASTM D445
Viscosity Index	172	ASTM D2270
Flash Point, °C (°F)	226 (439)	ASTM D92
Pour Point, °C (°F)	-45 (-49)	ASTM D97
Specific Gravity @ 60 °F	0.841	ASTM D4052
HTHS Viscosity @ 150 °C, cP	3.62	ASTM D5481
Sulfated Ash, % wt	< 0.8	ASTM D874

Made in the USA by TRIAX LLC © Copyright © 2026, all rights reserved. Other trademarks shown are the property of their respective owners. They are used only for descriptive purposes and communicate specification compliance, per industry standards and normative fair use laws. No affiliation or endorsement claim is made by their use.

TRIAX LLC - 1405 S. Belt Line Rd, Suite 200, Coppell, TX 75019 - www.triaxlubricants.com