



HMIS

Health Hazard	0
Fire Hazard	1
Reactivity	0

This SDS is in accordance with US 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) or the Canadian Workplace Hazardous Material Information System (WHMIS 2015)

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product Name</b>	<b>Leather Conditioner</b>
<b>Recommended Use</b>	Cleans, Restores and Protects Leather
<b>Manufactured by:</b>	TRIAX LLC 1405 S Belt Line Rd, Ste 200, Coppell, TX 75019 Phone: 214-897-6533
<b>Emergency Telephone Number</b>	CHEMTREC 1 (800) 424-9300 International: +011(703) 527-3887

## 2. HAZARDS IDENTIFICATION

### Emergency Overview

<b>Appearance</b>	Light Blue	<b>Physical State</b>	Lotion	<b>Odor</b>	Leather
<b>Physical hazards</b>	None				
<b>Health hazards</b>	None				
<b>Environmental hazards</b>	None				
<b>Human health</b>	Not Classified				
<b>Environmental</b>	Not Classified				

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Wt %
Naphtha (petroleum), heavy alkylate	64741-65-7	9-20
Stoddard solvent	8052-41-3	5-18
Xylene	1330-20-7	1-5
Petroleum Distillates, Hydrotreated light	64742-47-8	1-5
Morpholine	110-91-8	1-5
Methanol	67-56-1	1-5
Isopropanol	67-63-0	1-5
Ethylbenzene	100-41-4	0.2-1.2

#### 4. FIRST-AID MEASURES

<b>Eye Contact</b>	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
<b>Skin Contact</b>	Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/ attention.
<b>Inhalation</b>	Remove to fresh air.
<b>Ingestion</b>	Call a poison control center or physician immediately. Do not induce vomiting.
<b><u>Important Effects &amp; Symptoms</u></b>	Causes skin irritation and serious eye damage. May be harmful or fatal if swallowed and enters airways.

#### 5. FIRE-FIGHTING MEASURES

<b>Suitable Extinguishing Media</b>	Water. Foam. Dry chemical. Carbon dioxide (CO2).
<b>Unsuitable Extinguishing Media</b>	Not determined.
<b>Hazardous Combustion Products:</b>	Combustible liquid. Can form explosive mixture at temperature at or above the flash point.  Carbon oxides (CO, CO2). On heating: release of toxic and corrosive gases/vapors sulphur oxides.
<b>Protective equipment and precautions for firefighters</b>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
<b><u>NFPA</u></b>	<b>Health Hazard</b> 0 <b>Flammability</b> 1 <b>Stability</b> 0 <b>Physical and Chemical Hazards</b> -

#### 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions</b>	Use personal protection recommended in Section 8.
<b>Environmental Precaution</b>	Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 13: DISPOSAL CONSIDERATIONS.
<b>Clean Up Procedures</b>	Contain and collect with an inert absorbent and place into an appropriate container for disposal.

#### 7. HANDLING AND STORAGE

<b>Handling</b>	Handle according to good industrial hygiene and safety practices. Use recommended PPE (see Section 8). Avoid contact with skin, eyes, and clothing; wash thoroughly after handling. Do not eat, drink, or smoke when using. Avoid inhaling dust, fumes, gas, mist, vapors, or spray. Read and understand all safety precautions before use. Keep away from heat, sparks, open flames, and hot surfaces. No smoking.
-----------------	---

**Storage and Incompatible Materials**

Keep container tightly closed and store in a cool, dry and well-ventilated place. Store locked up. Do not allow to freeze. Store between 4°C (40°F) and 35°C (95°F). Shelf life: one year.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Naphtha (petroleum), heavy alkylate 64741-65-7	100 ppm	500 ppm 2900 mg/m <sup>3</sup>	-
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m <sup>3</sup>	IDLH: 20000 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	-
Morpholine 110-91-8	TWA: 20 ppm S*	TWA: 20 ppm TWA: 70 mg/m <sup>3</sup> (vacated) TWA: 20 ppm (vacated) TWA: 70 mg/m <sup>3</sup>  (vacated) STEL: 30 ppm (vacated) STEL: 105 mg/m <sup>3</sup> (vacated) S*	IDLH: 1400 ppm TWA: 20 ppm TWA: 70 mg/m <sup>3</sup> STEL: 30 ppm  STEL: 105 mg/m <sup>3</sup>
Methanol 67-56-1	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m <sup>3</sup> (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m <sup>3</sup> (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 325 mg/m <sup>3</sup>
Isopropanol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>

**Exposure Guidelines**

**Engineering Controls**

Ensure adequate ventilation, especially in confined areas. Eyewash stations. Showers.

**Individual Protection Measures**

**Eye/Face Protection**

Safety goggles or safety glasses with side shields.

**Skin and Body Protection**

Wear nitrile or vinyl gloves. Wear suitable protective clothing.

**Respiratory Protection**

NIOSH-approved respirator or mask in the absence of adequate ventilation.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Light Blue	<b>Odor</b>	Leather
<b>Physical State</b>	Cream Lotion	<b>pH</b>	8 - 9
<b>Flash Point</b>	40 C / 104 F	<b>Autoignition Temperature</b>	Not Available
<b>Boiling Point</b>	Not Determined	<b>Freezing Point</b>	Not Available
<b>Explosion Limits</b>	N/A	<b>Lowest Flammability Limits in Air</b>	Not Available
<b>Specific Gravity</b>	0.820 – 0.860 gm/ml	<b>Solubility</b>	Will mix with water

### 10. STABILITY AND REACTIVITY

<b>Reactivity</b>	Not reactive under normal conditions.
<b>Chemical Stability</b>	Stable under recommended storage conditions.
<b>Conditions To Avoid</b>	Avoid high temperatures. Keep out of reach of children.
<b>Incompatible Materials</b>	None known based on information supplied.
<b>Hazardous Decomposition</b>	Carbon monoxide. Carbon dioxide (CO2).

### 11. TOXICOLOGICAL INFORMATION

<b>Eyes &amp; Skin</b>	Causes severe skin burns and eye damage.
<b>Inhalation</b>	Avoid breathing vapors or mists.
<b>Ingestion</b>	May be fatal if swallowed and enters airways. May be harmful if swallowed.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Naphtha (petroleum), heavy alkylate 64741-65-7	> 7000 mg/kg (Rat)	> 3000 mg/kg (Rat) > 2000 mg/kg (Rabbit)	> 5.04 mg/L (Rat) 4 h
Xylene 1330-20-7	4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	5000 ppm (Rat) 4 h 47635 mg/L (Rat) 4 h
Petroleum Distillates, Hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Morpholine 110-91-8	1050 mg/kg (Rat)	310 mg/kg (Rabbit)	-
Methanol 67-56-1	5628 mg/kg (Rat)	15800 mg/kg (Rabbit)	83.2 mg/L (Rat) 4 h 64000 ppm (Rat) 4 h
Isopropanol 67-63-0	4396 mg/kg (Rat)	12800 mg/kg (Rat) 12870 mg/kg (Rabbit)	72.6 mg/L (Rat) 4 h
Ethylbenzene 100-41-4	3500 mg/kg (Rat)	15354 mg/kg (Rabbit)	17.2 mg/L (Rat) 4 h

**Germ cell mutagenicity** May cause genetic defects.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen. However, the product as a whole has not been tested.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	Not Available	Group 3	Not Available	Not Available
2-Butoxyethanol 111-76-2	Not Available	Group 3	Not Available	Not Available
Sodium hydroxide 1310-73-2	Not Available	Group 3	Not Available	X
Ethylenediaminetetraacetic acid 60-00-4	A3	Group 2B	Not Available	X

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Naphtha (petroleum), heavy alkylate 64741-65-7	30000: 72 h Pseudokirchneriella subcapitata mg/L EC50	Not Available	Not Available	2: 48 h Mysidopsis bahia mg/L LC50
Xylene 1330-20-7	Not Available	13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static	EC50 = 0.0084 mg/L 24 h	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50
Petroleum Distillates, Hydrotreated light 64742-47-8	Not Available	45: 96 h Pimephales promelas mg/L LC50 flow-through 2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static	Not Available	Not Available
Morpholine 110-91-8	28: 96 h Pseudokirchneriella subcapitata mg/L EC50	350: 96 h Lepomis macrochirus mg/L LC50 static 375 - 460: 96 h Oncorhynchus mykiss mg/L LC50 1000: 96 h Brachydanio rerio mg/L LC50 static	EC50 = 57.0 mg/L 30 min	100: 24 h Daphnia magna mg/L EC50

Methanol 67-56-1	Not Available	28200: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through	Not Available	Not Available
Isopropanol 67-63-0	1000: 96 h Desmodemus subspicatus mg/L EC50 1000: 72 h Desmodemus subspicatus mg/L EC50	9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96 h Pimephales promelas mg/L LC50 static 1400000: 96 h Lepomis macrochirus µg/L LC50	Not Available	13299: 48 h Daphnia magna mg/L EC50
Ethylbenzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

### 13. DISPOSAL CONSIDERATIONS

**Disposal of Wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging** Disposal should be in accordance with applicable regional, national and local laws and regulations.

#### US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7	-	Included in waste stream: F039	-	U239
Methanol 67-56-1	-	Included in waste stream: F039	-	U154
Ethylbenzene 100-41-4	-	Included in waste stream: F039	-	-

#### California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Xylene 1330-20-7	Toxic Ignitable
Methanol 67-56-1	Toxic Ignitable
Isopropanol 67-63-0	Toxic Ignitable
Ethylbenzene 100-41-4	Toxic Ignitable

**14. TRANSPORT INFORMATION**

- Note** According to 49 CFR §173.150(f)(1), this material should be reclassified as "NA1993, Combustible Liquid, N.O.S." if it is shipped in bulk.
- DOT** Not regulated
- IATA** Not regulated
- IMDG/IMO** This material may meet the definition of a marine pollutant

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA** All ingredients are listed or exempt from listing on Chemical Substance Inventory

**U.S. Federal Regulations**

**CERCLA**

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Methanol 67-56-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Ethylbenzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

**SARA 313**

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Xylene	1330-20-7	1-5	1.0
Methanol	67-56-1	1-5	1.0
Isopropanol	67-63-0	1-5	1.0
Ethylbenzene	100-41-4	0.2-0.12	0.1

**CWA (Clean Water Act)**

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7 ( 1-5 )	100 lb			X
Ethylbenzene 100-41-4 ( 0.2-1.2 )	1000 lb	X	X	X

**U.S. State Regulations – California Proposition 65**

This product contains chemical(s) known to the state of California to cause cancer and or birth defects. Additional information can be received upon request.

Chemical Name	California Proposition 65
Methanol - 67-56-1	Developmental
Ethylbenzene - 100-41-4	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Stoddard solvent 8052-41-3	X	X	X
Xylene 1330-20-7	X	X	X
Morpholine 110-91-8	X	X	X
Methanol 67-56-1	X	X	X
Isopropanol 67-63-0	X	X	X
Ethylbenzene 100-41-4	X	X	X

**16. OTHER INFORMATION**

**Prepared By** TRIAX, LLC  
**Revision Date** April 04, 2025  
**Revision Note** None

**Disclaimer**

The information provided on this MSDS is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End MSDS