

TRIAX SYNERGY DXR 0W-40

FULL SYNTHETIC GM DEXOS R ENGINE OIL

TRIAX Synergy DXR 0W-40 is a full synthetic, high-performance engine oil engineered exclusively for gasoline engines requiring the GM Dexos R specification. This formulation was developed in response to the GM 0W-20 Dexos R recall, which identified the need for a more robust oil to ensure long-term protection of high-output turbocharged gasoline engines. With enhanced viscosity stability, high film strength, and advanced oxidation resistance, TRIAX Synergy DXR 0W-40 is designed to withstand the extreme conditions of modern turbocharged gasoline direct-injection (GDI) engines. It delivers superior wear control, piston cleanliness, and LSPI protection while maintaining efficiency and reliability under severe driving conditions.

TRIAX Synergy DXR 0W-40 is Ideal for North American sports cars, such as the Corvette, with outstanding high temp stability and wear protection both on the track and for every day driving.

PERFORMANCE HIGHLIGHTS

- Exceeds GM Dexos R specification requirements
- Excellent cold-start lubrication & pumpability To -50°C
- Superb high temp film strength, oxidation stability & durability
- Extended drain capabilities up to 15,000 or two years (whichever comes first)
- Built-In Friction Modifiers for Unmatched Turbo-Charger & Engine Protection, with a 68% Lower Friction Coefficient
- Unmached protection for off-road heavy duty service
- For Use in All GM Dexos R Applications in U.S. Vehicles; including but Not Limited to Corvette, Camaro ZL1, Escalade-V, CTS-V & Other GM Performance Models

Up to

15,000 miles**

Or 2 Years drain interval

**100% OEM
COMPLIANCE**

APPLICATIONS & SPECIFICATIONS

This product meets or exceeds the requirements of:

**GM Dexos R
API SP**

Application Details:

2019-2024 Chevrolet Silverado 1500 Dodge RAM with Hurricane HO
2019-2024 GMC Sierra 1500
2021-2024 Chevrolet Suburban
2021-2024 Chevrolet Tahoe
2021-2024 Cadillac Escalade
2021-2024 GMC Yukon
2021-2024 GMC Yukon XL

If a specification is listed above, TRIAX LLC guarantees the product meets, exceeds that specification or recommends the product for use in that specification. Our product warranty covers those applications.

CHEMICAL PROPERTIES

VISCOSITY GRADE SAE	0W-40
SPECIFIC GRAVITY @ 60F	0.844
KINEMATIC VISCOSITY @ 40C	~69 cst
KINEMATIC VISCOSITY @ 100 C	~13 cst
VISCOSITY INDEX	~192
FLASH POINT (C)	232
POUR POINT C(F)	-51 (-59)

Small deviations from these results are expected during the manufacturing process and do not affect product performance.

*All trademarked names are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use, which is strictly to guide consumers as to the application of TRIAX products and convey compatibility or lack thereof.

** The drain interval mentioned herein represents the capability of the lubricant and is valid for a mechanically sound engines, with regular oil analysis and without the use of after-market additives.