

TRIAX EURO LV 0W-20



FULL SYNTHETIC EUROPEAN CAR DIESEL AND SELECT GASOLINE ENGINES

TRIAX EURO LV 0W-20 Full Synthetic is a low viscosity, low friction engine oil designed for the latest generation of BMW, VW / Audi and Mercedes engines requiring a 0W-20 full synthetic. This is a high PAO / Ester content product, with an exceptionally low volatility, superb low temp properties and extreme shear stability. It is a top tier product in all respects, surpassing OEM oil performance standard. This product contains supplemental friction modifiers for improved protection of critical parts, drastically improving the life of turbo-chargers, pistons and bearings.

PERFORMANCE HIGHLIGHTS

- Excellent shear stability, low volatility and extended drain intervals
- Low temperature pumpability down to -50°C
- State-of-the detergent system to keep your engine clean for 250,000 miles and beyond
- Exceptionally quiet and efficient hydraulic tappets
- Excellent protection for turbo-chargers, preventing premature failure due to oil deposits
- Nearly ZERO deposits on piston rings and valves throughout its life
- Complete protection for Catalytic Converters, Diesel Particulate Filters & SCR (AdBlue) systems
- Maintains film integrity even at very high operating temperatures
- Permits full service for vehicles still in OEM warranty per the specifications listed below.

EXTENDED DRAIN INTERVAL
15,000 miles or 2 Years**
whichever comes first

APPLICATIONS

This product is designed for late generation diesel and gasoline BMW, Mercedes Benz, Volvo, VW and Audi vehicles requiring a 0W-20 engine oil. It is also compatible with any gasoline vehicle requiring an API SN or SN Plus engine oil as well as select Ford engines.

SPECIFICATIONS

VW / Audi 508.00 & 509.00 (Approval Pending)
Porsche C20
API SN and API SN Plus
VW TL 52577

This product IS NOT backwards compatible with VW 504.00 / 507.00 or any other VW Specifications

Additional Applications

ACEA C5
MB 229.71
BMW Longlife-17 FE+
BMW Longlife-14 FE
Volvo VCC RBS0-2AE
STJLR.03.5006
STJLR.51.5122

If a specification is listed above, TRIAX LLC guarantees the product meets, exceeds that specification or recommends the product for use in that specification. Our product warranty covers those applications.

CHEMICAL PROPERTIES

VISCOSITY GRADE SAE	5W-40
SPECIFIC GRAVITY @ 60F	0.849
KINEMATIC VISCOSITY @ 40C	41
KINEMATIC VISCOSITY @ 100 C	8.1
VISCOSITY INDEX	176
SULFATED ASH %	<1.0
HTHS (cp)	>2.60
FLASH POINT (C)	234
POUR POINT C (F)	-54 (-65.2)

Small deviations from these results are expected during the manufacturing process and do not affect product performance.

*All trademarked names are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use, which is strictly to guide consumers as to the application of TRIAX products and convey compatibility or lack thereof.

** The drain interval mentioned herein represents the capability of the lubricant and is valid for a mechanically sound engines, with regular oil analysis and without the use of after-market additives.