

| NFPA | HMIS          |   |
|------|---------------|---|
|      | Health Hazard | 0 |
|      | Fire Hazard   | 1 |
| < Y  | Reactivity    | 0 |

#### This SDS Is in accordance with US 2012 OSHA Hazard Communication Standard (29 CFR1910.1200) or the Canadian Workplace Hazardous Material Information System (WHMIS 2015)

## **1. PRODUCT AND COMPANY IDENTIFICATION**

| Product Name               | TRIAX Powerflow MV ISO 32, 46, 68  |
|----------------------------|--|
| Recommended Use            | Hydraulic System<br>Not for use in internal combustion engines                       |
| Manufactured by:           | TRIAX LLC<br>751 Port America, Suite 810. Grapevine, TX 76051<br>Phone: 214-897-6533 |
| Emergency Telephone Number | CHEMTREC<br>1 (800) 424-9300<br>International: +011(703) 527-3887                    |

# 2. HAZARDS IDENTIFICATION

### **Emergency Overview**

#### Classification

This product is **not considered hazardous** by either the US 2012 OSHA Hazard Communication Standard (29 CFR1910.1200) or the Canadian Workplace Hazardous Material Information System (WHMIS 2015.

| Appearance Yellow liquid                                  | Physical<br>State   | liquid  | Odor                  | Petroleum odor |
|---|---|---|-----------------------|----------------|
| Potential Health Effects<br>Principal Routes of Exposure  | Eye contact, Skin co  | ontact, Inhalation, Ingestion   |                       |                |
| Acute Toxicity<br>Eyes<br>Skin<br>Inhalation<br>Ingestion | Substance minimally<br>Low hazard at stand<br>fumes can cause irr | sult in slight irritation and rednes<br>y irritating upon direct contact.<br>lard temperatures and pressures<br>itation of the nose, throat and up<br>tion may cause gastrointestinal | s. Inhala<br>per resp | iratory tract  |
| Other   | pulmonary disease   | prolonged and repeated exposu<br>such as chronic lung inflammatic<br>result of repeated small aspiratic   | on. This              |                |
| Chronic Effects   | Prolonged exposure  | e may cause chronic effects.  |                       |                |
| Aggravated Medical Conditions                             | Personnel with pre-eproduct.                                      | existing skin disorders should av   | void conta            | act with this  |



#### Environmental Hazard

See Section 12 for additional Ecological Information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Formula

Mixture

| Chemical Name                         | CAS-No                        | Weight % |
|---------------------------------------|-------------------------------|----------|
| Lubricant Base Oil (Petroleum) Highly | Mixture                       | 90-99.9% |
| refined mineral oils (C15-C50)        |                               |          |
| Hydraulic Oil Additive Mixture        | Proprietary and Confidential* | 0.1-10%  |

This product does not contain known hazardous materials at the  $\geq$  1% level or known carcinogens at the  $\geq$  0.1% level as defined by 29 CFR 1910.1200.

\* Exact % of composition is being withheld as a trade secret.

### 4. FIRST-AID MEASURES

| Eye Contact        | Flush with large amounts of water for 15 minutes. Get medical attention if eye irritation develops or persists. If material is hot, treat for thermal burns and take victim to the hospital immediately. |
|--------------------|--|
| Skin Contact       | Wash off immediately with soap and plenty of water for at least 15 minutes while removing all contaminated clothing and shoes. Get medical attention immediately if skin discoloration occurs.           |
| Inhalation         | This material is not expected to present an inhalation exposure at ambient conditions.   |
| Ingestion          | Never give anything by mouth to an unconscious person. Do not induce vomiting. Get immediate medical attention or advice.  |
| Notes to Physician | Treat symptomatically.   |

# 5. FIRE-FIGHTING MEASURES

| Flammable Properties   | NOT FLAMMABLE                      |
|--|------------------------------------|
| Flash Point  | >400 °F                            |
| Suitable Extinguishing Media   | Water fog, Foam, CO2, dry chemical |
| Unsuitable Extinguishing Media   | Not Available                      |
| Hazardous Combustion Products  | Not Available                      |
| <u>Explosion Data</u><br>Sensitivity to Mechanical Impact<br>Sensitivity to Static Discharge | Not sensitive<br>Not sensitive     |



| Protect<br>Firefigh | tive Equipment an<br>nters | nd Pr | ecautions for |   | appa<br>expo<br>cloth | iratus<br>sed t<br>ing w<br>ys ma | itive pressure self-contained breathing<br>s (SCBA). Use water to cool containers<br>to flames. Structural firefighters' protective<br>vill only provide limited protection. Mist or<br>ay be flammable below the product normal<br>t. |
|---------------------|----------------------------|-------|---------------|---|-----------------------|-----------------------------------|--|
| <u>NFPA</u>         | Health<br>Hazard           | 0     | Flammability  | 1 | Stability             | 0                                 | Physical and Chemical -<br>Hazards   |

|  | 6. | ACCIDENTAL | <b>RELEASE MEASURES</b> |
|--|----|------------|-------------------------|
|--|----|------------|-------------------------|

| Personal Precautions                         | Use personal protective equipment. Avoid contact with skin, eyes, and clothing.<br>Ensure adequate ventilation. If spilled, take caution, as material can cause surfaces<br>to become very slippery.  |
|--|---|
| Methods for Containment                      | Dike far ahead of liquid spill for later disposal.  |
| Methods for Cleaning Up                      | Pick up free liquid for recycle and/or disposal. Residual liquid and/or solid can be absorbed on inert material.  |
| Evacuation Procedures<br>Large Spill<br>Fire | Consider initial downwind evacuate for at least 300 meters (1000 feet).<br>If tank, rail car or tank car is involved in a fire, isolate for 800 meters (1/2 mile) in all<br>directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. |
| Reporting Requirements                       | Spills that enter a water body must be reported immediately to the USEPA's National Response Center at (800)424-8802. Check with your local and state regulators regarding their reporting requirements.  |

# 7. HANDLING AND STORAGE

| Handling | Do not pressure, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode. See NFPA 30 and OSHA 1910.106 – flammable and combustible liquids. |
|----------|---|
| Storage  | Store away from heat, sparks, open flame, or strong oxidizing agents in closed and properly labeled containers. Empty containers retain product residue (liquid, and/or vapor) and can be dangerous   |

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

| Chemical Name              | ACGIH TLV                | OSHA PEL                 | NIOSH IDLH  |
|----------------------------|--------------------------|--------------------------|-------------|
| Lubricant Base Oil         | 5 mg/m3 8 hour(s). Form: | 5 mg/m3 8 hour(s). Form: | 2,500 mg/m3 |
| (Petroleum) Highly refined | Mist                     | Mist                     |             |
| mineral oils mixture       |                          |                          |             |
| Detergent/Inhibitor System |                          | 5 mg/m3 8 hour(s). Form: |             |
| Mixture                    |                          | Mist                     |             |

### **Engineering Measures**

Additional area ventilation or local exhaust may be required to maintain air concentrations below recommended limits.



### **Personal Protective Equipment**

| Eye/Face Protection                                   | Safety glasses or face shield where splashing is possible. Full face-shield to be worn during emergencies.   |
|---|--|
| Skin and Body<br>Protection<br>Respiratory Protection | As needed to prevent repeated skin contact. Solvent resistant gloves should be used if needed.<br>Not normally needed. During emergencies wear respirator. |

**Hygiene Measures** 

Remove and wash contaminated clothing before re-use. Wash hands before breaks and immediately after handling the product.

#### PHYSICAL AND CHEMICAL PROPERTIES 9.

Green liquid Appearance **Physical State** Flash Point

**Explosion Limits** 

**Specific Gravity** 

Vapor Density

**Evaporation Rate** 

Liquid >400 °F **Boiling Point/Range** No data

N/A 0.86 - 0.88N/A Not Determined

Odor рΗ Autoignition Temperature **Freezing Point** Flammability Limits in Air Solubility Vapor Pressure Density

Mild Petroleum Odor N/A >315°C /600°F

<-40°C /°F N/A

Negligible < 0.01 N/A

### **10. STABILITY AND REACTIVITY**

| Stability                           | STABLE under recommended storage conditions and room temperature.  |
|-------------------------------------|--|
| Incompatible Products               | Open Flame and strong oxidizing agents.  |
| Conditions to Avoid                 | Heat, flames, and sparks.  |
| Hazardous Decomposition<br>Products | Combustion products may include smoke, fumes, oxides of phosphorus, boron, sulfur, nitrogen, carbon dioxide, carbon monoxide, and other low molecular weight hydrocarbons. |
| Hazardous Polymerization            | None under normal processing.  |

### **11. TOXICOLOGICAL INFORMATION**

#### THIS PRODUCT IS NON-HAZ FOR STORAGE AND TRANSPORTATION

| Product Information         | Test on similar materials show a low order of acute oral and dermal toxicity.   |
|-----------------------------|---|
| Acute Oral<br>Effects       | Test on similar materials indicates low order of acute toxicity.  |
| Acute Inhalation<br>Effects | Low acute toxicity expected on inhalation.  |
| Skin Effects                | Practically non-toxic if absorbed. Other similar highly refined products have not shown skin tumors in mouse skin painting studies. |
| Eye Irritation              | Minimal irritation on contact. Eye irritation slightly or practically non-irritating base on similar products.                      |



#### **Component Information**

| Chemical Name              | LD50 Oral   | LD50 Dermal  | LC50 Inhalation            |  |
|----------------------------|---|--|----------------------------|--|
|                            | LD50 Oral   | LD50 Dermai  | LC50 Initialation          |  |
| Lubricant Base Oil         |   |  |                            |  |
| (Petroleum) Highly refined | Not Available   | Not Available  | Not Available              |  |
| mineral oils mixture       |   |  |                            |  |
|                            |   |  |                            |  |
| Chronic Toxicity           |   |  |                            |  |
| Chronic Toxicity           | repeated exposure to oil mis  | use chronic effects. On rare o<br>t poses a risk of pulmonary di<br>i is usually asymptomatic as a | sease such as chronic lung |  |
| Carcinogenicity            | Not considered a potential carcinogen base on IP346 DMSO of less than 3.0 wt%   |  |                            |  |
| Target Organ Effects       | Respiratory system, Eyes, Skin,   |  |                            |  |
| Genotoxicity               | This product is considered non-mutagenic and has negative potential for tumor development based on from Modified Ames Assay, with Mutagenic Index of less than 1.0. |  |                            |  |
|                            | 12. ECOLOGIC  | AL INFORMATION   |                            |  |

**Ecotoxicity** If applied to leaves, this product may kill grasses and small plants by interfering with transpiration and respiration. This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration. This product may cause gastrointestinal distress to birds and mammals through ingestion during pelage grooming.

| Chemical Name   | Toxicity to<br>Algae | Toxicity to Fish | Microtox      | Daphnia Magna<br>(Water Flea) |
|---|----------------------|------------------|---------------|-------------------------------|
| Lubricant Base Oil<br>(Petroleum) Highly<br>refined mineral oils<br>mixture | Not Available        | Not Available    | Not Available | Not Available                 |

### **13. DISPOSAL CONSIDERATIONS**

| Waste Disposal Method  | Dispose of in accordance with local regulations. Keep this product out of sewers and waterways. |
|------------------------|---|
| Contaminated Packaging | Dispose of in accordance with local regulations.  |

# 14. TRANSPORT INFORMATION

DOT Not regulated

IATA Not regulated

IMDG/IMO Not regulated



### **15. REGULATORY INFORMATION**

#### International Inventories

| TSCA | DSL | EINECS/ELINCS | ENCS | IECSC | KECL | PICCS | AICS |
|------|-----|---------------|------|-------|------|-------|------|
| Х    | Х   | Х             | Х    | Х     | Х    | Х     | Х    |

#### U.S. Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

#### SARA 311/312 Hazard Categories

| Acute Health Hazard        | No |
|----------------------------|----|
| Chronic Health Hazard      | No |
| Fire Hazard                | No |
| Sudden Release of Pressure | No |
| Hazard                     |    |
| Reactive Hazard            | No |

#### Clean Water Act

If spilled into navigable waters it is reportable to National Response Center, 800-424-8802. Reportable Quantity = Oil Sheen present on navigable water surface. (40 CFR 116; 401.15)

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

#### CERCLA

#### U.S. State Regulations

#### California Proposition 65

This product does not contain any Proposition 65 chemicals. **Florida** No listed ingredients are present **Massachusetts RTK** No listed ingredients are present **Minnesota RTK** No listed ingredients are present **New Jersey RTK** Lists petroleum oil, but this product does not contain hazardous ingredients. **Pennsylvania RTK** Lists petroleum oil, but this product does not contain hazardous ingredients greater than 3%. **Illinois DOL TSL** No listed ingredients are present

#### International Regulations

Mexico – Grade No information available.



| Canada       | Not listed on the Car<br>with Controlled Prod                                    | nadian Controlled Product Ingredient Disclosure and is compliant<br>lucts Regulation  |
|--------------|--|---|
| CONEG Metals |  | omium, lead, and mercury are not detectable and it does not exceed product, it is compliant with CONEG Metals regulation.   |
| EEC (Europe) | This product is not k<br>R-Phrases<br>S-Phrases<br>Hazard Label<br>Danger Symbol | nown to be a dangerous good internationally.<br>R45: May Cause Cancer<br>S53: Avoid exposure - obtain special instructions before use.<br>S45: In case of accident or if you feel unwell, seek medical advice<br>immediately (show the label where possible).<br>None<br>None |

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

# **16. OTHER INFORMATION**

Prepared By TRIAX, LLC

Revision Date March 11, 2024

Revision Note None

Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End MSDS